

SYSTEM FOR DISPLAYING A MAP

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a system for displaying a map using a mobile (portable) terminal device.

2. Description of the Related Art

One of the information providing services offered by cellular telephone companies or affiliated companies is transmitting map data to a cellular phone so that a map is displayed in a display screen of the cellular phone. In general, a data server can include map data to provide map data of various areas. When a user of a cellular phone operates the cellular phone to specify a desired area, information about the specified area is transmitted by wireless communication to a data server from the cellular phone. Then, map data that matches the specified area information is transmitted by wireless communication back to the cellular phone from the data server so that a map of the desired area is displayed in the display screen of the cellular phone.

A user of a mobile or portable terminal device such as a cellular phone usually sees a map when the user visits an unfamiliar place. The user often does not know which direction is the north or south. The map is generally displayed in the cellular phone screen with the top of the map being directed to the north. Unless the user knows which direction is the north, the displayed map is difficult to use.

SECRET

According to a first aspect of the present invention, there is provided a system for displaying a map in a display unit of a mobile terminal device, the system comprising a terminal detector for detecting if the mobile terminal device exists in a first region on a path, a transmitter for transmitting map data representing a map of and around the first region to the mobile terminal device when the terminal detector detects that the mobile terminal device exists in the first region, a receiver for receiving the map data from the transmitter, and a controller for causing the display unit to display the map based on the map data received by the receiver such that a top of the map is aligned with a top of the display unit.

2

0907995-11601

According to a third another aspect of the present invention, there is provided a method of displaying a map in a display unit of a mobile terminal device, comprising the steps of (A) detecting if the mobile terminal device exists in a first region on a path, (B) transmitting map data representing a map of and around the first region to the mobile terminal device when existence of the mobile terminal device in the first region is detected in Step A, (C) receiving the map data, and (D) causing the display unit to display the map based on the received map data such that a top of the displayed map is aligned with a moving direction of the mobile terminal device.

According to a fourth aspect of the present invention, there is provided a system for displaying a map in a display unit of a mobile terminal device, comprising a first terminal detector for detecting if the mobile terminal device exists in a first region on a path, a second terminal detector for detecting if the mobile terminal device exists in a second region other than the first region on the path, a first transmitter for transmitting first map data representing a first map of and around the first region to the mobile terminal device when the first terminal detector detects that the mobile terminal device exists in the first region, a second transmitter for transmitting second map data representing second map of and around the second region to the mobile terminal device when the second terminal detector detects that the mobile terminal device exists in the second region, a receiver for receiving the first map data from the first transmitter and the second

09087995 114504

map data from the second transmitter, and a controller for causing the display unit to display the first or second map based on the first or second map data received by the receiver such that a top of the displayed first or second map is aligned with a moving direction of the mobile terminal device.

According to a fifth aspect of the present invention, there is provided a host device for transmitting map data to a mobile terminal device, comprising a first terminal detector for detecting if the mobile terminal device exists in a first region on a path, a second terminal detector for detecting if the mobile terminal device exists in a second region other than the first region on the path, a first transmitter for transmitting first map data representing a first map of and around the first region to the mobile terminal device when the first terminal detector detects that the mobile terminal device exists in the first region, and a second transmitter for transmitting second map data representing second map of and around the second region to the mobile terminal device when the second terminal detector detects that the mobile terminal device exists in the second region.

According to a sixth aspect of the present invention, there is provided a method of displaying a map in a display unit of a mobile terminal device, comprising the steps of (A) detecting if the mobile terminal device exists in a first region on a path, (B) detecting if the mobile terminal device exists in a second region other than the first region on the path, (C) transmitting first map data representing a map of and around

0098795 11501

the first region to the mobile terminal device when presence of the mobile terminal device in the first region is detected in Step A, (D) transmitting second map data representing a map of and around the second region to the mobile terminal device when presence of the mobile terminal device in the second region is detected in Step B, and (E) receiving at least one of the first and second map data and causing the display unit to display the map based on the received map data such that a top of the displayed map is aligned with a moving direction of the mobile terminal device.

According to a seventh aspect of the present invention, there is provided a mobile terminal device comprising a display unit, a receiver for receiving map data, a controller for causing the display unit to display a map based on the map data received by the receiver, and a direction detector for detecting a direction of the mobile terminal device, wherein the controller converts the received map data on the basis of the direction of the mobile terminal device detected by the direction detector such that the map is displayed in a particular direction regardless of the direction of the mobile terminal device.

According to an eight aspect of the present invention, there is provided a mobile terminal device comprising a display unit, a receiver for receiving map data, and a controller for causing the display unit to display a map based on the map data received by the receiver, wherein when the receiver receives first map data of a first cell within a predetermined period

after receiving second map data of a second cell other than the first cell, the controller ignores the first map data and causes the display unit to keep displaying the map based on the second map data.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a block diagram of a map displaying system according to one embodiment of the present invention;

Figure 2 illustrates a map around a ground entrance/exit of a subway together with two cells used by the system shown in Figure 1;

Figure 3 illustrates a sequence diagram for displaying a map executed by the system shown in Figure 1;

Figure 4 illustrates a map displayed in a portable terminal device of the system shown in Figure 1;

Figure 5 illustrates two cells defined at an entrance/exit of a department store when the system shown in Figure 1 is designed for a portable terminal device user who enters and exits the department store;

Figure 6 illustrates a block diagram of a map displaying system according to another embodiment of the present invention;

Figure 7 illustrates a sequence diagram for displaying a map executed by the system shown in Figure 6;

Figure 8 illustrates a block diagram of a map displaying system according to still another embodiment of the present invention;

Figure 9 illustrates a map of T-shaped intersection

09987905-44604

0997995-44604
109445628550

together with three cells used by the system shown in Figure 8;

Figures 10 and 11 illustrate a flowchart of operation executed by the system shown in Figure 8 to show a map in a portable terminal device;

Figure 12 illustrates a block diagram of a portable terminal device used in a system for displaying a map according to yet another embodiment of the present invention;

Figure 13 illustrates an appearance of the portable terminal device shown in Figure 12;

Figure 14 illustrates a block diagram of operation executed by the map displaying system to display a map in the portable terminal device shown in Figure 12; and

Figure 15 illustrates an appearance of a modified portable terminal device.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention will be described in reference to the accompanying drawings.

Referring to Figure 1, illustrated is a system for displaying a map according to a first embodiment of the present invention. The map displaying system includes a host device 1 and a portable (mobile) terminal device 2. The host device 1 may be located on the ground adjacent to an entrance/exit of a subway. The host device 1 provides wireless (radio) communication with the portable terminal device 2. A technique in compliance with the Bluetooth standard is employed as the wireless (radio) communication technique.

09087995 144504

As shown in Figure 1, the host device 1 includes two Bluetooth transmission/reception units 11 and 12, a control circuit 13 and a memory device 14. Each of the Bluetooth transmission/reception units 11 and 12 is a unit for transmitting and receiving signals in compliance with the Bluetooth standard and has an antenna 11a, 12a. The antennas 11a and 12a possess different directivities. An area (region) of signal transmission and reception by the antenna 11a is a semicircular, first cell, and an area of signal transmission and reception by the antenna 12a is a semicircular, second cell. The first and second cell are independent from each other. The memory device 14 stores map data in the form of image data. The map data includes two kinds of maps. One map is a ground map that shows a plat on the ground, with a direction towards a ground entrance/exit from a underground passage(way) of a subway system being at the top of the map. The other map is an underground map that shows a plat under the ground, with the direction towards the underground from the ground entrance/exit being at the top of the map. The maps indicate streets, banks, hotels, department stores, shops, and other conspicuous buildings with their names. The control circuit 13 reads the map data from the memory device 14 when the first Bluetooth transmission/reception device 11 receives a signal from a remote Bluetooth machine such as the portable terminal device 2. The control circuit 13 then causes the first Bluetooth transmission/reception device 11 to transmit the map data to the Bluetooth machine.

The portable terminal device 2 is a mobile terminal machine that has a cellular phone function. As schematically illustrated in Figure 1, the portable terminal device 2 includes a telephone signal transmission/reception part 31, a Bluetooth transmission/reception part 32, a display unit 33, an operation unit 34, a memory 35, and a control circuit (CPU) 36. The telephone transmission/reception unit 31 for wireless telephone communication has an antenna 31a, a microphone 37 and a speaker 38. The microphone 37 and speaker 38 are provided for telephone conversation. The Bluetooth transmission/reception device 32 is a signal transmission and reception unit that conforms to the Bluetooth standard. An antenna 32a extends from the Bluetooth transmission/reception device 32. The control circuit 36 is connected to the telephone transmission/reception unit 31, Bluetooth transmission/reception device 32, display 33, control panel 34 and memory 35, and controls the overall operations of the portable terminal device 2.

When a user of the portable terminal device 2 walks upstairs from an underground passage(way) of a subway and enters the area of the first cell as shown in Figure 2, the portable terminal device 2 subscribes for a piconet as shown in Figure 3 (Step S1). The host device 1 is a master and the portable terminal device 2 is a slave in the piconet. A subscription procedure for the piconet is defined in the Bluetooth standard so that the subscribing procedure will not be described here. The first Bluetooth transmission/reception device 11 in the host device 1 is activated to communicate with the Bluetooth

transmission/reception device 32 in the portable terminal device 2 for the piconet subscription.

After the subscription procedure for the piconet is complete, the control circuit 13 of the host device 1 reads map data, which shows a ground map suited for the user present in the first cell, from the memory device 14 (Step S2), and causes the Bluetooth transmission/reception device 11 to send the map data to the portable terminal device 2 (Step S3).

Upon receiving the map data, the Bluetooth transmission/reception device 32 of the portable terminal device 2 transfers the map data to the control circuit 36. The control circuit 36 transfers the map data to the display unit 33 and causes the display unit 33 to display the map such that the top of the map is shown at the top of the display unit 33 (Step S4). The display 33 of the portable terminal device 2 shows the map as depicted in Figure 4. The top of the displayed map corresponds to the direction towards the ground exit from the underground facility.

It should be noted that the map displaying operation may not be done automatically, but by a certain operation made onto the control panel 34 by the user.

On the other hand, when the user of the portable terminal device 2 on the ground walks into the second cell area (Figure 2) in order to step down into the underground facility, the portable terminal device 2 subscribes for the piconet (Step S1), as in the case of stepping up to the ground from the underground facility. The second Bluetooth transmission/reception device

12 of the host device 1 is then activated to communicate with the Bluetooth transmission/reception device 32 of the portable terminal device 2 for the piconet subscription.

After completing the subscribing procedure for the piconet, the control circuit 13 of the host device 1 reads map data, which shows an underground map suited for the user present in the second cell, from the memory device 14 (Step S2). The control circuit 13 then causes the Bluetooth transmission/reception device 12 to send the map data to the portable terminal device 2 (Step S3).

When the Bluetooth transmission/reception device 32 of the portable terminal device 2 receives the map data, the Bluetooth transmission/reception device 32 supplies the map data to the control circuit 36. The control circuit 36 supplies the map data to the display unit 33 and causes the display unit 33 to show the subway facility map (underground map) such that the top of the map is shown at the top of the display screen (Step S4). The top of the displayed map corresponds to the direction from the ground entrance to the underground facility. The top of the display screen 33 is generally directed in a direction in which the user of the portable terminal device 2 is walking (downward arrow in Figure 2). The user is walking downstairs in this instance.

If the portable terminal device 2 immediately moves from the area of the first cell to the area of the second cell, the map data of ground map is transmitted to the portable terminal device 2 and subsequently a new piconet is established between

(mobile) terminal devices existing in the same cell as the portable terminal device 2.

The above described system for displaying a map is applicable when the user enters or exits a department store. Referring to Figure 5, the semicircular first cell outside the entrance/exit of the department store is used as the signal transmission/reception area of the antenna 11a and the opposite semicircular cell (second cell) inside the entrance/exit of the department store is used as the signal transmission/reception area of the antenna 12a. The map data stored in the memory device 14 include a map of a first floor inside the department store and a map of streets outside the department store. The top of the map of the first floor is aligned with the perpendicular direction from the outside of the department store to the inside through the entrance/exit (direction in which the user of the portable terminal device 2 perpendicularly walks into the department store through the entrance/exit). The top of the map of the streets is aligned with the perpendicular direction from the inside of the department store to the outside. When the user of the portable terminal device 2 outside the department store walks towards the entrance/exit of the department store and steps in the first cell, the procedure shown in Figure 3 is carried out so that the map of the sales floor (first floor) inside the department store is shown in the display screen 33 of the portable terminal device 2. The control circuit 36 causes the display to display the map such that the top of the map coincides with the top of the

090799 562850
F09F 4404

display screen. When the user of the portable terminal device 2 inside the department store walks towards the entrance/exit of the department store and steps in the second cell, on the other hand, the procedure shown in Figure 3 takes place so that the map of the streets outside the department store is shown in the display screen 33 of the portable terminal device 2. The control circuit causes the display 33 to display the map such that the top of the map coincides with the top of the screen.

Referring to Figure 6, illustrated is a system for displaying a map that is activated in accordance with different floors of the department store. In general, the department store has more than one floor and a customer goes to different floors by an elevator. The illustrated system can show maps of different floors, and includes a host device 41, a portable terminal device 42 and a control circuit 43 of an elevator 44. The elevator control circuit 43 causes the elevator 44 to move up and down in accordance with an operation made by a person in the elevator so as to stop the elevator 44 at a desired floor.

The host device 41 is similar to the host device 1 shown in Figure 1 except for having only one Bluetooth transmission/reception device. The host device 41 includes a Bluetooth transmission/reception device 51, a control circuit 53 and a memory device 54. An antenna 51a of the Bluetooth transmission/reception device 51 is provided in the elevator cage 44, but other elements of the host device 41 may be provided either inside or outside the elevator cage 44. The host device control circuit 53 is coupled with the elevator control circuit 43 via

an interface (not shown). The elevator control circuit 43 supplies data of floor, on which the user of the portable terminal device 42 desires to get off, to the host device control circuit 53. The memory device 54 stores map data of respective floors in the department store. The top of the each floor map is aligned with the perpendicular direction from the inside of the elevator to the floor.

The portable terminal device 42 has a structure similar to the portable terminal device 2 shown in Figure 1. Specifically, the portable terminal device 42 includes a telephone signal transmission/reception unit 61, a Bluetooth transmission/reception unit 62, a display unit 63, an operation unit 64, a memory 65, a control circuit 66, a telephone microphone 67 and a telephone speaker 68. Like the system shown in Figure 1, wireless communication takes place between the host device 41 and portable terminal device 42 using the Bluetooth technique. The interior of the elevator cage 44 is an area of signal transmission and reception (i.e., cell) covered by the antenna 51a.

Referring to Figure 7, a subscribing operation of the portable terminal device 42 for the piconet is executed when the user of the portable terminal device 42 steps into the elevator cage 44 (Step S11). In the piconet, the host device 41 is a master and the portable terminal device 42 is a slave. The Bluetooth transmission/reception device 51 of the host device 41 is activated to communicate with the Bluetooth transmission/reception device 62 of the portable terminal

third map data shows an underground map such that the top of the map coincides with the direction from the third cell to the intersection.

The portable terminal device 2 shown in Figure 1 is used in the system shown in Figure 8.

Operation of the portable terminal device 2 for displaying a map when the user of the portable terminal device 2 walks in the intersection along the path P1 or P2 will be described.

Referring to Figure 10, the control circuit 36 of the portable terminal device 2 determines whether the portable terminal device 2 exists in the first cell (Step S31). If the portable terminal device 2 exists in the first cell, the control circuit 36 can obtain information of existence of the portable terminal device 2 in the first cell from the host device 71 because the portable terminal device 2 performs the subscribing operation for the piconet. Likewise, if the portable terminal device 2 exists in the second (or third) cell, the control circuit 36 can obtain information of existence of the portable terminal device 2 in the second (or third) cell from the host device 71.

When the portable terminal device 2 is present in the first cell, the portable terminal device 2 receives first map data from the host device 71 (Step S32). The first map data is map data suited for the user in the first cell. An underground map derived from the first map data is then displayed in the display screen 33 of the portable terminal device 2 (Step S33). The

control circuit 36 causes the display to show the map such that the top of the map coincides with the top of the display screen. The top of the map is aligned with the direction from the first cell to the intersection.

After Step S33, the control circuit 36 determines whether the portable terminal device 2 is present in the second cell (Step S34). In other words, Step S34 determines whether the user of the portable terminal device 2 who has stepped out the first cell now walks into the second cell by making the left turn at the intersection. If the portable terminal device 2 (or the user) exists in the second cell, the first map data received at Step S32 is converted to map data suited for the user in the second cell (Step S35). Specifically, the first map data is converted such that the map in the screen 33 of the portable terminal device 2 is turned 90 degrees to the right. The map prepared from the converted map data is then displayed in the screen 33 (Step S36). The top of the map in the screen 33 coincides with the direction from the intersection to the second cell because the control circuit 36 causes the display to show the 90-degree turned map such that the new top of the map is aligned with the top of the display screen.

When the control circuit 36 determines at Step S34 that the portable terminal device 2 does not exist in the second cell, the control circuit 36 then determines whether the portable terminal device 2 exists in the third cell (Step S37). In other words, it is determined whether the user of the portable terminal device 2 walks from the first cell to the third cell

by making the right turn at the intersection. If the portable terminal device 2 is present in the third cell, the first map data received at Step S32 is converted (Step S38). Specifically, the map data is converted such that the map is turned 90 degrees to the left in the screen 33 of the portable terminal device 2. The map prepared from the converted map data is then displayed in the screen 33 (Step S39). The top of the map coincides with the direction from the intersection to the third cell.

If the control circuit 36 determines at Step S37 that no portable terminal device 2 exists in the third cell, the program returns to Step S34 to determine whether the portable terminal device 2 exists in the second cell.

When it is determined at Step S31 that the portable terminal device 2 does not exist in the first cell, the control circuit 36 determines whether the portable terminal device 2 exists in the second cell (Step S40, Figure 11). If the portable terminal device 2 is present in the second cell, the portable terminal device 2 receives second map data from the host device 71 (Step S41). The second map data is map data suited for the user of the portable terminal device in the second cell. A map prepared from the second map data is then displayed in the screen 33 of the portable terminal device 2 (Step S42). The top of the displayed map is aligned with the direction from the second cell to the intersection.

After Step S42, the control circuit 36 determines whether the portable terminal device 2 exists in the first cell (Step

S43). In other words, it is determined whether the user of the portable terminal device 2 walks in the first cell from the second cell by making the right turn at the intersection. If the portable terminal device (or the user) exists in the first cell, the second map data received at Step S41 is converted (Step S44). Specifically, the second map data is converted such that the map in the screen 33 of the portable terminal device 2 is turned 90 degrees. The map prepared from the converted second map data is then displayed in the screen 33 (Step S45). The top of the map coincides with the direction from the intersection to the first cell (or the path P1).

If the control circuit 36 determines at Step S43 that the portable terminal device 2 does not exist in the first cell, the control circuit determines whether the portable terminal device 2 exists in the third cell (Step S46). In other words, it is determined whether the user of the portable terminal device 2 walks straight into the third cell from the second cell. When the portable terminal device 2 is present in the third cell, the direction (posture) of the currently displayed map is maintained.

When the control circuit 36 determines at Step S46 that the portable terminal device 2 does not exist in the third cell, the program returns to Step S43 to determine again whether the portable terminal device 2 exists in the first cell.

When the control circuit 36 determines at Step S40 that the portable terminal device 2 does not exist in the second cell, the control circuit determines whether the portable terminal

transmission/reception unit 31, a Bluetooth transmission/reception device 32, a display unit 33, an operation unit 34, a memory 35, a control circuit (CPU) 36, a microphone 37, a speaker 38 and the geomagnetic sensor 39. As illustrated in Figure 13, the geomagnetic sensor 39 is located below the display 33 on the front face of the portable terminal device 40. A reference direction of the geomagnetic sensor 39 is the north, and the geomagnetic sensor 39 detects the direction of the portable terminal device 40, i.e., in which direction the head of the portable terminal device 40 is pointing.

When the user of the portable terminal device 40 walks upstairs from the underground (subway walkway) towards the ground and enters the first cell (Figure 2), the portable terminal device performs the subscribing operation for the piconet (Step S1) as shown in Figure 3. The Bluetooth transmission/reception device 11 of the host 1 is then activated to communicate with the Bluetooth transmission/reception device 32 of the portable terminal device 40 for the piconet subscription. Upon completing the piconet subscribing operation, the control circuit 13 of the host device 1 reads map data suitable for the user in the first cell from the memory device 14 (Step S2) and causes the Bluetooth transmission/reception device 11 to transmit the map data to the portable terminal device 40 (Step S3).

Upon receiving the map data (Step S61 in Figure 14), the Bluetooth transmission/reception device 32 of the portable terminal device 40 supplies the map data to the control circuit

that the direction from the underground walkway to the ground entrance/exit always is aligned with (matches) the direction of the map displayed in the screen 33 regardless of the direction of the portable terminal device 40.

When the user of the portable terminal device 40 enters the second cell (Figure 2) to step downstairs to the underground, a map of the underground is displayed in the screen 33. The top of the map always is aligned with the direction from the ground entrance/exit of the underground walkway to the underground regardless of the direction of the portable terminal device 40.

Although the geomagnetic sensor 39 is provided as the direction detection means for the portable terminal device 40 in the above described embodiment, other types of direction detection means may be employed. For instance, a CCD camera 91 and four rods 92a to 92d may be provided in or on the portable terminal device 40 as illustrated in Figure 15. The four rods 92a to 92d are located around a lens of the CCD camera 91 at equal intervals. Shadows of the rods 92a to 92d made on the portable terminal device 40 by the sunlight, moonlight or particular starlight (e.g., light from the North Star) are detected by the CCD camera 91 when the portable terminal device 40 is held horizontally. The direction of the portable terminal device 40 is then calculated on the basis of relationship between the shadows of the sunlight (or moonlight or particular starlight) and day-and-time. The relationship between the shadows of the sunlight (or moonlight or particular starlight)

and day-and-time is stored in the portable terminal device beforehand.

It should be noted that although the wireless communication technique in compliance with the Bluetooth standard is utilized for the communication between the host device and portable terminal device in the above described embodiments, other wireless communication technique such as IrDA (Infrared Data Association), HomeRF (Home Radio Frequency) and IEEE 802.11 may be utilized. The rods 92a to 92d may be replaced with any projections as long as the projections can make shadows.

As described above, the system of the present invention displays a map such that the moving direction of the portable terminal device is aligned with the top of the displayed map. Therefore, a user of the portable terminal device can easily understand relationship between a moving direction of the user and the top of the map (direction of the map) in the display.

This application is based on Japanese Patent Application No. 2000-352508, and the entire disclosure thereof is incorporated herein by reference.

0987995-11501